


Lightning¹⁶⁻¹⁴²⁹

16 Channel High Speed Data Acquisition System



Connect | Condition | Acquire

Key Features

- 16 Voltage & IEPE Conditioned Channels in 2U Form Factor
- 16-bit ADC, >95dB SNR, 250kHz—10MHz Sample Rates
- 10Gigabit Ethernet Connectivity
- Conduction Cooled, Milled Unibody Chassis
- Modular Architecture, Scalable to >1000 Channels
- Multi-unit Synchronisation (GPS, IRIG, LVDS, IEEE-1588)
- 9-36V dc & PoE++ Power Options

Lightning¹⁶⁻¹⁴²⁹




16 Channel High Speed Data Acquisition System

Introduction

Lightning is a series of rugged 16-channel high-speed data acquisition modules designed to provide a world class, highly flexible solution for high bandwidth data measurement.

The Lightning series features 10Gigabit Ethernet connections, allowing control from remote laptops or PCs, as well as data streaming for monitoring / archiving.

Lightning is designed to operate in extreme environments, operating at altitudes to 60,000ft (20,000m), in temperatures from -55 to 80°C, and humidity to 100% RH at measurement uncertainties of < +/-0.5%.of reading.



The Lightning¹⁶⁻¹⁴²⁹ supports Voltage, IEPE (with TEDS support) inputs directly via IP68 capable BNC / Lemo 2-pin connectors..

The Lightning¹⁶⁻¹⁴²⁹ is supplied as standard with both IEEE-1588 and IRIG A/B support for synchronising the unit with external devices to +/-20ns accuracy. A GPS receiver can be specified as an optional addition.

Multiple power options are provided as standard, including Power over Ethernet (PoE++) to the latest IEEE802.3bt standard (HGL can also supply matching Power Injector units), 9-36V dc and wide range mains via external adaptors (100-250V ac 50/60Hz unit supplied).

All communications with the unit is achieved via Ethernet through the rear-mounted LEMO ports. HGL can supply software support from an API through to fully featured measurement systems.

Lightning¹⁶⁻¹⁴²⁹



16 Channel High Speed Data Acquisition System

Hardware Overview

Unibody Chassis

Rugged, milled aluminium housing for use in close proximity to the test article. External cooling fins are milled into the body to aid in heat dissipation. All internal PCBs mounted to thermal pads integrated into the chassis,

Connector Compatibility

Standard options available are BNC, LEMO2, or LEMO8 pin. HGL can also provide customer specific connectors on request.




No Moving Parts

All components are securely mounted internally directly to the unibody chassis. No fans. No rotating storage. Solid State electronics.

Independent Inputs

Equipped with 16 individual channels
One SAR ADC per channel.
Multiple Conditioning Options.
Simultaneous Sampling.
>114 dB SNR.

16_{CH}



Buffered Analogue Outputs


Buffered outputs from the HGL-1429 conditioning (one output per 8 channels)

Calibration

Hummingbird facilitates quick on-board correction with the use of standard bench signal generators/multi-meters.

IRIG (GPS Option) Synchronisation

Dedicated IRIG-A/B input for synchronization with external systems.
Optional GPS input for high precision synchronisation



Networking

- Command & Control Interface
- 2x10Gigabit data streaming
- 1x1Gigabit data streaming
- IEEE-1588 Synchronisation

LVDS Synchronisation

- LVDS (Low Voltage Differential Signalling) Synchronisation Interface
- <10nS Unit to Unit
- 0-200m Unit to Unit cable lengths Daisy-Chain, Star or mixed topologies

DC Power

- 9-36V d.c.
- Slave output connectors for additional units

Lightning¹⁶⁻¹⁴²⁹



16 Channel High Speed Data Acquisition System

Specification

General

Dimensions (W x H x D):	485 x 89 x 60 mm
Weight:	5 kg (typical)
Supply Voltage:	9-36V V DC
	PoE++ (IEEE 802.3bt)
Power:	40 W (typical)

Environmental

Operating Temp.:	-55 to +80 °C
Operating Pressure:	Above 4.8 kPa (limit 24 hrs)
Storage Temp:	-55 to 100°C
Relative Humidity:	0-100% RH (IP68)

Input Configuration (with standard 1418 signal conditioning card)

Input Channels:	16
ADC Type:	SAR
Quantization:	16-bit
Input Ranges:	±50mV to ±100V in 1, 2, 5 steps*
DC Offset:	±0.15 mV
Input Coupling:	AC, DC *
Input Impedance:	>1MΩ
SNR:	>95 dB
Anti-aliasing:	<-100dB
Sample Rate:	250kHz - 10MHz *
Frequency Response:	DC to >500 kHz ± 0.1 dB
Dynamic Range:	105 dBFS / √Hz, 95 dB (broadband)
Inter-Channel Δ Phase:	< 20 nS (< 0.36° @ 10 kHz output signal)
Crosstalk:	< 100 dB @ 5 kHz, < 95 dB @ 10 kHz, < 87 dB @ 20 kHz, < 82 dB @ 40 kHz, < 70 dB @ 100 kHz
Distortion:	< -70 dB, 0 to 100 kHz
DC Linearity:	< 0.01%
Drift:	< 25 ppm/°C (with no correction applied)

Accuracy (%full scale)

Standard (50kHz 1V rms)	
Voltage.:	±0.25%
IEPE:	±0.5%
Charge (SE/DF—optional):	±0.5%

Frequency Response (0-100kHz)	
V, IEPE,	±0.1dB
Charge (SE/DF—optional):	±0.2dB

Temperature Response (Calibrated)	
All Types (-30 to +80°C):	±0.25%

Altitude Response	
All Types (0 to 20,000m):	±0.25%

*Software configurable parameter

Synchronisation

LVDS:	±50 ns
LVDS (max distance)	200 m # (node to node)
IRIG A/B:	±100 ns
IEEE-1588:	±20 ns
GPS (optional)	±50 ns

#If longer distances are require please contact HGL

Other Inputs (using any standard input)

IRIG-A and IRIG-B
Tachometer / Flow meter



Software Options

HGL Dynamics provides multiple software platforms for Hummingbird Acquisition systems; these range from low level Network APIs, Windows[®] DLL, Single Instrument Applications (Apps), and full Measurement System software. This flexibility allows users to choose the best platform for their particular applications and / or increases the utilisation of the hardware for multiple uses.

External Integration Protocols


Integrating HGL's software into a third party system has never been easier. HGL Dynamics offers multiple ways to communicate with the Acquisition Software suites. Communication options include DDS subscriber / publisher, OPC client / server and Modbus (over ethernet) client / server.

Network API

All HGL Dynamics hardware modules are Ethernet connected to each other and their host PC(s); a fully documented Programmer's API is available for integrators / customers who wish to access the modules at this level or need to integrate the modules with a non-Windows operating system.

Microsoft Windows DLL


HGL provides (as standard) a Windows DLL with every Hummingbird Acquisition System; for Microsoft Windows users this provides a simpler method to access all the functions of the hardware.



Single Instrument Apps

HGL has developed a number of Single Instrument Apps, primarily for its Firefly system. These apps can be operated on a Hummingbird and Laptop / PC system equally well. The Apps are intended to provide a family of simple, easy to use applications which turn the Hummingbird into a single instrument, examples include:

- FFT Analyser
- Oscilloscope
- Chart Recorder
- Rotating Machinery Analyser
- Trim Balance
- Power Dip & Rise
(requires isolation amplifier hardware)



Full Measurement System Software

For the past 26 years, HGL has providing a fully integrated, modular, network distributed Dynamics Measurement System; this software is intended for wide variety of applications and for systems ranging from small portable units to large multi-site systems with hundreds or thousands of channels.

The System comprises four main parts, Acquisition, Monitoring, Analysis and Data Management, and is focused on providing robust, flexible, fixed or mobile operation with ease of use as a primary consideration.



Software Suites

Data Acquisition - Hawk

HGL's Hawk acquisition software provides everything a user needs to configure, calibrate and acquire data from the acquisition hardware. Full control and feedback of the system is provided by the Hawk GUI Client application; this provides an intuitive instrument-like interface that allows even novice users to operate large channel count systems, even from remote locations.



Real-Time Monitoring - Hawkeye



Hawkeye allows one or more users to monitor the signals being acquired in real-time (<0.1s latency).

Fully customisable displays such as FFTs, Waterfalls, Oscilloscopes, Numerical, Speed and Tracked-orders, Phase, Bode, Orbit, n^{th} Octave etc, provide a rich monitoring environment.

Hawkeye also provides Time, Frequency, Order and Phase domain alarming facilities for all channels simultaneously, with support for many different alarms types per channel. Hawkeye is also client / server based with the 'thin' Hawkeye Client allowing local or remote monitoring (performance dependent on network infrastructure).

Analysis - Aurora

Aurora provides an in-depth analysis tool for acquired data; this is usually required post-test, but can be operated simultaneously with testing if useful. Post-test analysis can pinpoint areas of interest / problems to be further investigated, and for this purpose Aurora provides a range of client / server based tools to analyse, investigate, mine, summarise and report on acquired data.

Multiple users can use Aurora simultaneously, and in common with HGL software portfolio access is via a network connected thin-client (Aurora Client) application, thus allowing both local and (potentially widely) remote users to access data simply and efficiently.



Data Storage & Archiving - Hercules



Prolonged or large-scale data acquisition generates a lot of data, 10's and 100's of TBytes are not unusual for large enterprises. Data is expensive to collect and the functionality to efficiently store and retrieve legacy data is essential for in-service investigations, product development etc.

HGL's Hercules software provides an integrated, low-cost, yet highly scalable and safe data management solution for any sized data acquisition operation. The key to the system's success is support for virtually any common media type (SD cards, HDD/SSDs, LTO tapes etc.) combined with a unique database architecture providing simple, yet highly efficient data storage information, and a client/server architecture which allows data to be managed across multiple remote sites from a single intuitive Graphical User Interface.

Lightning¹⁶⁻¹⁴²⁹



16 Channel High Speed Data Acquisition System

Training

Training

HGL Dynamics offers a wide variety of training workshops and courses. Workshops are conducted at one of our global offices or at the client's site by our training team, all of whom have many years' of industry experience and knowledge.

Typical training courses include: Vibration Fundamentals, Signal Processing, Rotating Machinery, Advanced use of HGL Software and Analysing Large Datasets.



Information

About HGL Dynamics

HGL Dynamics is a world-leading supplier of services and high specification equipment for the integrated capture, monitoring, analysis, storage and management of high bandwidth data.

Purchasing & Availability

The HGL Dynamics Lightning Data Acquisition Module is now available for purchase or lease. Please contact one of our HGL Dynamics offices below for further information or to request a quote.

UK & International

HGL Dynamics Ltd
Hamilton Barr House
Bridge Mews
Godalming
GU7 1HZ
UK

Tel +44 1483 415177

France

HGL Dynamics France
25 Rue du Mont Olivet
78500 Sartrouville
France

Tel +33 1 75 93 80 20

Germany

ErTeMes GmbH
Brandenburger Str. 3
15738 Zeuthen
Germany

Tel +49 (0) 162 3313078

North America

HGL Dynamics Inc
2461 Directors Row
Suite J
Indianapolis
IN 46241
USA

Tel +1 317 782 3500

South Korea

HGL Dynamics South Korea
768 Posvill Officetel
Gumi-dong, Bundang-gu
Seongnam-si
Gyeonggi-do
Korea
483-861

Tel +82 109 052 2638



FS72209



Company registered in England No. 3844513